



PNEUMATIC | T-900

HEAVY-DUTY PERFORMANCE

PERFORMANCE DEFINED



TIRE LIFE

Trelleborg products guarantee **the best wear** performance in the industry. This results in longer tire life, **additional hours of usage**, reduced downtime and lower maintenance costs.



STABILITY

Trelleborg tires are designed with **exceptional stability**. Our tires are engineered to ensure **proper distribution of heat** and to prevent excessive deflection under load.



ENERGY SAVING

Trelleborg is the **largest approved tire manufacturer to the OEMs**. We work closely with them to ensure we meet the requirements of energy consumption. This results in **reduced fuel costs** for our customers.



COMFORT

Trelleborg recognizes the importance of a **safe working environment**. Our products are designed to minimize vibration and **keep noise to a minimum level**. We follow the strictest regulations for work safety while providing a comfortable ride.

TRELLEBORG T-900

The T-900 pneumatic tire was designed for heavy duty use on forklifts and other industrial equipment.

The T-900 provides an excellent total value of ownership. The reinforced sidewall, flat tread and special compounding provide for longer tread life and extra resistance against side impacts. It's the preferred tire of OEMs and the premium choice for today's aggressive applications.



T-900

Tire Size	PR	Rim	Pattern	Tire Weight	Tread Depth	Width	Overall Diameter	Inflation Pressure	Counterbalanced Forklift Truck: load capacity up to 25km/h		Other Vehicles: load capacity @ 10 km/h
									Load Wheels	Steer Wheels	
				[kg]	[mm]	[mm]	[mm]	[bar]	[kg]	[kg]	[kg]
5.00-8	10	3.00D-8	T-900	6.6	13	140	468	10.0	1415	1090	1415
18x7-8	16	4.33R-8	T-900	9.1	16	168	462	10.0	2145	1650	2145
6.00-9	12	4.00E-9	T-900	10.2	15	160	543	10.0	1885	1450	1885
6.50-10	12	5.00F-10	T-900	12.7	18	182	590	9.0	2145	1650	2145
23x9-10	20	6.50F-10	T-900	24.1	19	230	585	10.0	3445	2650	3445
23x10-12	20	8.00G-12	T-900	24.2	22	245	600	10.0	3770	2900	3770
7.00-12	14	5.00S-12	T-900	17.4	18	191	680	9.0	2755	2120	2755
7.00-12	16	5.00S-12	T-900	17.6	18	191	680	10.0	2910	2240	2910
27x10-12	16	8.00G-12	T-900	28.6	22	250	685	8.0	3900	3000	3900
27x10-12	24	8.00G-12	T-900	32.7	22	250	685	10.4	5040	3875	5040
7.00-15	14	5.5-15	T-900	20.6	20	204	760	8.8	3275	2520	3275
7.50-15	16	6.0-15	T-900	29.6	21	215	778	10.0	3900	3000	3900
28x9-15 (8.15-15)	14	7.0-15	T-900	26.6	18	230	710	10.0	3900	3000	3900
8.25-15	14	6.5-15	T-900	33.9	19	247	841	8.0	4225	3250	4225
8.25-15	16	6.5-15	T-900	36.9	19	247	841	9.3	4615	3550	4615
250-15	20	7.0-15	T-900	35.1	19	240	742	10.0	5040	3875	5040
300-15	20	8.0-15	T-900	44.6	23	290	840	9.0	6500	5000	6500
355/65-15	24	9.75-15	T-900	59.7	29	334	843	10.0	7800	6000	7800
7.50-16	12	6.0-16	T-900	29.6	21	220	805	8.0	3630	2790	3630
9.00-20	14	7.0-20	T-900	52.5	27	265	1015	9.0	5850	4500	5850
10.00-20	16	7.5-20	T-900	64.0	32	294	1085	9.0	6500	5000	6500
11.00-20	18	8.0-20	T-900	83.6	33	302	1110	10.0	7800	6000	7800
12.00-20	20	8.5-20	T-900	90.1	35	325	1145	10.0	8970	6900	8970
12.00-20	24	8.5-20	T-900	95.1	35	325	1145	10.4	9710	7470	9710
12.00-24	20	8.5-24	T-900	100.0	35	320	1245	10.0	9750	7500	9750
12.00-24	24	8.5-24	T-900	104.5	35	320	1245	10.4	9945	7650	9945
14.00-24	24	10.0-24	T-900	138.9	39	380	1360	10.0	12350	9500	12350
14.00-24	28	10.0-24	T-900	141.2	39	380	1360	10.4	12600	9690	12600

