



## RESILIENT | EcoSolid

**EcoSolid is an entry level solid tire option available in the 8" to 15" size range.**

**EcoSolid is designed for use on forklifts in light duty applications.**

- ▶ Available only in standard black compound
- ▶ Bead wires to avoid rim slippage
- ▶ Wear indicator built in to lug design

### ECOSOLID RANGE

Tire Size	Rim	Width [mm]	Overall Diameter [mm]	Counterbalanced Forklift Truck: load capacity up to 25 km/h		Other Vehicles:	
				Load Wheels [kg]	Steer Wheels [kg]	Load Capacity @ 10 km/h [kg]	Load Capacity @ 25 km/h [kg]
<b>5.00-8</b>	3.00D-8	122	457	1420	1090	1290	1090
<b>15x4½-8</b>	3.00D-8	103	372	1040	800	945	800
<b>16x6-8</b>	4.33R-8	140	409	1495	1150	1360	1150
<b>18x7-8</b>	4.33R-8	145	457	2145	1650	1950	1650
<b>6.00-9</b>	4.00E-9	140	508	1885	1450	1710	1450
<b>21x8-9</b>	6.00E-9	185	508	2755	2120	2500	2120
<b>140/55-9</b>	4.00E-9	127	370	1170	900	1060	900
<b>6.50-10</b>	5.00F-10	163	559	2340	1800	2125	1800
<b>200/50-10</b>	6.50F-10	186	447	2470	1900	2240	1900
<b>23x9-10</b>	6.50F-10	190	571	3445	2650	3125	2650
<b>7.00-12</b>	5.00S-12	168	660	2920	2240	2645	2240
<b>23x10-12</b>	8.00G-12	224	571	3770	2900	3420	2900
<b>27x10-12</b>	8.00G-12	230	656	3900	3000	3540	3000
<b>250-15</b>	7.0-15	216	711	4745	3650	4310	3650
<b>300-15</b>	8.0-15	254	810	5850	4500	5310	4500
<b>28x9-15 (8.15-15)</b>	7.0-15	204	686	3445	2650	3125	2650
<b>8.25-15</b>	6.50-15	206	787	4750	3650	4300	3650
<b>355/65-15</b>	9.75-15	279	808	7800	6000	6430	5450

\*In accordance to ETRTO Standard